

# SAFETY RULES FOR CORDLESS IMPACT

## WRENCHES



- **Select the correct size sockets and keep the inside of the socket clean.**

- **Do not allow a loose fastener to spin freely within the socket. The fastener may be thrown out of the socket.**

- **Use thick cushioned gloves and limit the exposure time by taking frequent rest periods.** Vibration caused by impact driver action may be harmful to your hands and arms.

- **Remove battery pack before changing accessories.**

Accidental starting may occur because battery appliances with a battery inserted are in the operative condition.

- **Be prepared for a reaction torque when “seating” or removing a fastener.** The tool housing may tend to twist in the opposite direction of accessory rotation

when “seating” or removing a fastener depending on the torque setting of the tool.

- **Do not run the tool while carrying it at your side.** The rotating drive could become entangled with clothing and injury may result.
- **Place the tool onto the fastener only when the tool is switched off.** Rotating driver tools can slide off the fastener.
- **Hold the power tool by insulated gripping surfaces, when performing an operation where the fastener may contact hidden wiring.** Fasteners contacting a “live” wire may make exposed metal parts of the power tool “live” and could give the operator an electric shock.
- **Use clamps or another practical way to secure and support the workpiece to a stable platform.** Holding the work by hand or against your body leaves it unstable and may lead to loss of control.
- **Do not drive fasteners into existing walls or other blind areas where electrical wiring may exist.** If this situation is unavoidable, disconnect all fuses or circuit breakers feeding this worksite.
- **Use only sockets designed for power impact wrenches.** Sockets designed for hand use may break under the load this tool generates.
- **Be certain to seat the socket completely and securely on the output drive.**
- **Do not use worn or damaged sockets.**